



## Data Sheet CODESYS Control for emPC-A/iMX6 SL

The product extends the device software and allows end users to program a Janz Tec emPC controller with the CODESYS Development System (V3) – the free development environment for IEC 61131-3 applications.

### Product description

CODESYS Control for emPC-A/iMX6 SL is a runtime environment based on CODESYS V3 for implementing a PLC with the Linux-based, real-time capable industrial controller emPC-A/iMX6 from Janz Tec AG. After installation the product, the PLC can be engineered with the CODESYS Development System (V3) from 3S-Smart Software Solutions GmbH.

- Purchase of the applicable hardware from the company Janz Tec AG (<http://www.janztec.com>).
- Download of the product CODESYS Control for emPC-A/iMX6 SL from the CODESYS Store (<http://store.codesys.com>).
- Installation of the CODESYS PLC runtime environment on the hardware

### Benefits

- Suitable for controllers in all industries and sectors
- Comprehensive engineering solution with the free CODESYS Development System (V3), including extensive visualization options
- Efficient engineering with the products of the CODESYS Professional Developer Edition (code management via link to Apache Subversion, static code analysis, runtime measurement on the PLC, comprehensive test automation, methodical application development with UML diagrams)
- Compatible with additional add-on and products from the CODESYS Store

Detailed information can be found in the [CODESYS Online Help](#).

### Interfaces

- CODESYS OPC UA Server, extent of use depends on the application-based license used.

### Visualization

- CODESYS WebVisu, extent of use depends on the application-based license used.

## SL Extension

The SL Extension Package is included in the Runtime Package and offers additional functions:

- Integration of existing C code
- Implementation of external functions
- Support of start/stop switches
- Usage of local I/Os
- Use of external event tasks
- Connect persistent memories (Retains)

## Fieldbus support

- CODESYS CANopen Manager / Device
- CODESYS EtherCAT Master
- CODESYS EtherNet/IP Scanner / Adapter
- CODESYS J1939
- CODESYS Modbus TCP Master / Slave
- CODESYS Modbus Serial Master / Slave
- CODESYS PROFINET Controller / Device

## Product options

Further products can be licensed for a fee:

- CODESYS BACnet SL
- CODESYS KNX SL
- CODESYS Redundancy SL
- CODESYS SoftMotion
- CODESYS SoftMotion Light SL
- CODESYS TargetVisu SL

-

## Possible extensions

- CODESYS Softmotion SL
- CODESYS TargetVisu, for emVIEW-6T, -7W, -8W, or -12
- CODESYS SoftMotion Light SL
- CODESYS SoftMotion SL,
- CODESYS SoftMotion CNC+Robotics SL,
- CODESYS BACnet SL
- CODESYS Safety for EtherCAT Safety Module (for EL6900) SL

## General information

### Supplier:

CODESYS GmbH  
 Memminger Strasse 151  
 87439 Kempten  
 Germany

### Support:

<https://support.codesys.com>

This product includes a CODESYS Support Ticket, i.e. 1 hour of support of CODESYS. More details can be found in the CODESYS Store product: [CODESYS Support Ticket](#).

### Item:

CODESYS Control for emPC-A/iMX6 SL

### Item number:

2302000014

### Sales/Source of supply:

CODESYS Store  
<https://store.codesys.com>

### Included in delivery:

- Package for the CODESYS Development System including CODESYS Control, license agreement, online help and device description
- License Key

## System requirements and restrictions

<b>Programming System</b>	CODESYS Development System V3.5.17.0 or higher
<b>Supported Platforms/ Devices</b>	<ul style="list-style-type: none"> <li>• SY-EPC-64001 (emPC-A/iMX6 with an RS232 port and CAN interface)</li> <li>• SY-EPC-64002 (emPC-A/iMX6 with two CAN interfaces)</li> <li>• SY-EPC-64002 (emPC-A/iMX6 with four CAN interfaces)</li> </ul> <p>Note: Use the tool "Device Reader" to find out the supported features of your device (free of charge component of CODESYS Development System).</p>
<b>Additional Requirements</b>	See license agreement. After installation, the user is responsible for implementing and checking the

functionality of the combination of the software package and hardware according to device specifications.

- Janz Tec-Firmware: 1.6 (minimum requirement)
- Dynamic libraries needed by the CODESYS Control

Runtime binary:

- libm.so.6
- libpthread.so.0
- libdl.so.2
- librt.so.1
- libc.so.6
- libgcc\_s.so.1
- libQtCore.so.4
- libQtGui.so.4
- libQtNetwork.so.4
- libQtWebKit.so.4
- libQtSvg.so.4

---

#### Restrictions

Not released for use in containers or virtual machines (VMs)!

---

#### Licensing



ABL

Application based license: The CODESYS Control SL runtime system can be licensed with an application-based license.

The license is activated on a software-based license container (soft container) that is permanently bound to the device. Alternatively, the license can be stored on a CODESYS key (USB dongle).

Note: In demo mode, the software runs for two hours without a license. After that, a manual restart is required.

---

#### Required Accessories

Optional: CODESYS Key

---

*Note: Technical specifications are subject to change. Errors and omissions excepted. The content of the current online version of this document applies.*

Creation date: 2024-09-20