

# **CODESYS PROFIsafe V2.6**

Licence to use the PROFINET V2.6 host functionality including TCI-based tools and i-Par server for application-based CODESYS safety controllers.

## **Product description**

## Profisafe V2.6 licence for functional safe PLCs

The Profisafe V2.6 licence extends your application-based licence of the functional safe PLC to include support for the Profisafe Host safe protocol according to version 2.6. The licence allows the use of Profisafe V2.6 host on your application-based CODESYS safety controller and offers full compatibility with current field devices and network topologies that support this standard.

Advanced features include support for TCI-based parameterisation tools and the use of an i-Par server.

Installation and activation is done easily via the CODESYS License Manager. In combination with an application-based licence, the Profisafe V2.6 licence is a key component for PLC systems that combine both the highest safety standards and modern communication protocols in a scalable concept.

n/a

### **General information**

#### Supplier:

CODESYS GmbH Memminger Strasse 151 87439 Kempten Germany

#### Support:

Technical support is not included with this product. To receive technical support, please purchase a CODESYS Support Ticket.

https://support.codesys.com

Item:

CODESYS PROFIsafe V2.6

Item number:

2306000006

Sales/Source of supply:

CODESYS Store https://store.codesys.com

Included in delivery:

License only

### System requirements and restrictions

Programming System	<ul> <li>CODESYS Development System V3.5.20.0 or higher</li> <li>CODESYS Safety Extension AddOn V4.3.0.0 or higher</li> <li>CODESYS Profinet AddOn V4.6.0.0 or higher</li> </ul>
Runtime System	<ul> <li>CODESYS Virtual Control SL V4.14.0.0 or higher</li> <li>CODESYS Virtual Safe Control SL V4.14.0.0 or higher</li> </ul>
Supported Platforms / Devices	<ul> <li>CODESYS Virtual Safe Control SL</li> </ul>
Runtime System Updates	This product additionally includes a five-year update authorization. The five-year period starts with the activation of the License. The update authorization can be extended at any time.
Additional Requirements	Wibu CodeMeter runtime version 8.0 or higher
Restrictions	<ul> <li>Not released for use in containers or virtual machines (VMs)!</li> </ul>

• The license does not extend the number of safe connections. This license has to be used in conjunction with a CODESYS Safe Control license

	conjunction with a CODESYS Safe Control license
Licensing	ABL
	Application based license: The CODESYS Control SL runtime system can be licensed with an application-based license.
	The license is activated on a software-based license container (soft container) that is permanently bound to the device. Alternatively, the license can be stored on a CODESYS key (USB dongle).
Required Accessories	Optional CODESYS Key Version 3-xxxxxx

Note: Technical specifications are subject to change. Errors and omissions excepted. The content of the current online version of this document applies.

Creation date: 2025-01-21